

IN THE CLAIMS

Please amend the claims as follows:

1. (original) A display panel comprising a first substrate (2; 102) and a second substrate (3; 103) being separated from each other by spacers (4; 104) and sealing between them a space (7), at least one of the spacers (4; 104) being penetrated by a hole extending therethrough and through both of the substrates (2, 3; 102, 103) to form a through hole (5; 105; 205; 215) through the display panel (1; 100; 200), said at least one of the spacers (4; 104) and the substrates (2, 3; 102, 103) forming the wall (6; 106) of said through hole (5; 105) and sealing the space (7) from the through hole (5; 105).
2. (original) A display panel according to claim 1, in which each spacer (4) having a through hole (5) is located outside the pixel areas (11) of the display panel (1).
3. (currently amended) A display panel according to claim 1 ~~or 2~~, in which a plurality of through holes (5; 205), each extending through a respective one of the spacers (4) and through both of the substrates (2, 3) to form a through hole (5; 205) through the

display panel (1; 200), are distributed over the surface (218) of the display panel (1; 200).

4. (currently amended) A display panel according to ~~any one of claims 1-3~~claim 1, in which the spacers (4; 104) are made of a visually decorative material.

5. (currently amended) A display panel according to ~~any one of claims 1-4~~claim 1, in which the display panel is an LCD-display (1; 100; 200), a foil display, an electro-wetting display, a polyled display, a fluorescent display, or a touch screen or pressure-sensitive display.

6. (currently amended) A display panel according to ~~any one of claims 1-5~~claim 1, in which the display panel (100; 200) is flexible or bendable and/or has flexible substrates.

7. (currently amended) A display panel according to ~~any one of claims 1-6~~claim 1, in which the display panel (100) has a plastic (102, 103) or steel substrate.

8. (currently amended) A display panel according to ~~any one of claims 1-7~~claim 1, in which the display panel (200) is adapted to be integrated in a wearable product.

9. (original) A method of manufacturing a display panel, comprising the steps of

providing spacers (4; 104) on one side (17; 117) of a first substrate (2; 102),

providing a second substrate (3; 103) on said one side (17; 117) of the first substrate (2; 102) such that the spacers (4; 104) hold the first and the second substrates (2, 3; 102, 103) separated from each other,

forming a hole (5; 105) through at least one of the spacers (4; 104) and both of the substrates (2, 3; 102, 103) such that said at least one of the spacers (4; 104) and the substrates (2, 3; 102, 103) form the wall (6; 106) of the through hole (5; 105), and

sealing a space (7; 107) between the substrates (2, 3; 102, 103) and the spacers (4; 104).

10. (original) A method according to claim 9, in which said through hole (5; 105) is formed after the step of providing the second substrate (3; 103) on said one side (17; 117) of the first substrate (2; 102).

11. (original) A method according to claim 9, in which a liquid crystalline material (10) is sealed between the substrates (2, 3; 102, 103) and the spacers (4; 104) after the step of forming said through hole (5; 105).

12. (original) A method according to claim 9, in which a liquid crystalline material (10) is sealed between the substrates (2, 3; 102, 103) and the spacers (4; 104) before the step of forming said through hole (5; 105).

13. (original) A method according to claim 9, in which said through hole (5; 105) is formed by a method chosen among stamping, mechanical drilling, laser drilling, powder blasting and water jetting.

14. (currently amended) A method according to ~~any one of claims 9-13~~claim 9, in which the spacers (104) are made by ink jet printing monomers, polymers, reactive polymers or a mixture of two or three of these components (112) on the first substrate (102) followed by one or more curing steps.

15. (currently amended) A method according to ~~any one of claims~~
~~9-13~~claim 9, in which the spacers (4) are made by forming a
photosensitive film (12) on the first substrate (2) followed by
illumination and removal of those parts of the film (12)
surrounding those parts that are to become the spacers (4).